

1: Code:RFP80-E				
2: Eco-solvent Grey Back Removable PP				
Number	Item	Properties	units	Standard
3	Film	Thickness-film	um	80±7
5		Eco-solvent top coated	g/m ²	23-26
6		Top coated Color	/	white
7		color error	Δ E	≤1.5
8	PET Liner	weight-liner	Um	50±3
9	Glue	Adhesive	/	Grey & Removable
10		Loop tack	g/m ²	≥4N/in
11		Initial Adhesion*20 min peel strength (SS)	N/25mm	≥5
12		Cohesion	h	≥48
13		180°Peel strength(steel,24h) 180°	N/25mm	≥8
14		Strength of release	N/25mm	0.10-0.30
15	Dimensional stability		mm	CD≤1.5; MD≤1.8
18	Storage Temperature		°C	23±2
19	Storage Humidity		%	50±5
20	Shelf Life (unprinted)		Month	12
21	Gurantee Period		Month	12 (with little or no adhesive residue after removable)

*Print: Eco-solvent, Latex, UV

*Removable: There might be a risk of residue if peel off when temperature above 40°C or in the presence of a chemical agent, the repaired paint surface / oxidized iron plate or paint board.

*Lamination is recommended to protect image

*Not recommend to post it on curved surface.